


HD ANALOG IR MOTORIZED VF DOME CAMERA


DI-350AU-MVF



MODEL	DI-350AU-MVF
Image Sensor	1/2.8" CMOS
Image Format	16:9
Effective Pixels	2592(H)×1944(V)
Scanning System	Progressive
Resolution	Digital: 2560x1936 / Analog:960H
Min. Illumination	0.01Lux (0 Lux with IR on)
Day & Night	True Day&Night (ICR)
IR LED	3 LED Array (25m)
OSD Menu	Available
CoC Support	Yes
Day & Night Mode	EXT, Color, B&W, Auto
Backlight Compensation	Off/BLC/True WDR (120dB)
S/N Ratio	≥35dB (AGC Off)
White Balance	Auto, Manual
Noise Reduce	2D-DNR
Video Output	AHD / CVI (4MP Only) / TVI / CVBS + PAL/NTSC (Selectable by DIP switch)
Defog	No
Privacy Mask	No
Motion Detection	No
D-Effect	Mirror
Lens (Field of View)	2.8-12mm Motorized with Auto-Focus (90°-34°)
Power	DC12V±10%, ~400mA
Operation Temp.	-30°C~+50°C
Waterproof	IP66
Dimension	129.5*90*119mm
Net weight	476g

Main Features:

- Sensor: 1/2.8" CMOS, 5 Mega-Pixel
- Video Output: AHD / CVI / TVI / Analog
- Lens: 2.8-12mm Motorized with Auto Focus
- True Day & Night – ICR
- True WDR
- IR Range: 25m (3 Array LED)
- IP66
- CoC Support
- Weight: 476g
- Power: DC 12V, ~400mA



Junction Box (PR-B47JB) is available

DIP Switch for Output Selection