


40M IR MOTORIZED VF BULLET CAMERA

I4-390IP5MVF



1/2.7" CMOS Sensor
 2 Mega-Pixel
 True Day & Night (IR Cut Removable)
 H.265 (HEVC) Compression
 0 Lux (IR On) Min. Illumination

ONVIF
 True WDR / BLC / HLC
 3D Noise Reduction
 Motion Detection and Privacy Masking
 Analytics Support

3.3-12mm Motorized Lens with Auto-Focus
 40m IR Illumination
 PoE Support
 Local Storage
 RS-485
 I/O
 2 Way Audio
 Technician Port
 IP 66 Protection
 RS-485

Specifications (Based on v4.2.1)

Camera	Video	Model	I4-390IP5MVF
		Image Sensor	1/2.7" CMOS (16:9)
		Effective Pixels	1920x1080
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30FPS
	Audio	Day & Night	ICR
		Min. Illumination	Day: 0.022lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on
	Image Processing	Audio compression	G.711A/G.711U
		Communication	Two-way Audio
		Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
Image Enhancement		True WDR (120dB) / BLC / HLC / ROI	
Noise Reduction		3D-DNR	
Image Orientation		Mirror/Flip	
Privacy Zone		Yes	
Compression	Motion Detection	Yes	
	Analytics	Camera Tampering, Line Crossing, Sterile Area, Smart Search	
	Video Compression	H.265 / H.264 / MJPEG (Sub-Stream Only)	
	Resolution	1080P (1920x1080), 720P (1280x720), D1, CIF	
	Multi-Stream	11920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS)	
	Bit rate	64Kbps ~ 4Mbps@H.265 / 128Kbps ~ 6Mbps@H.264	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	40m (48 IR LED)
	Lens (Field of View)	3.3-12mm Motorized with Auto-Focus (109.8°-38.5°)
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis
Connectivity	Dimensions	Φ109mm×284mm
	Weight(gross)	1115g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS(BNCx1)
	Audio Connectivity	1Ch Input, 1Ch Output
	SD Card	Support Event recording over TF (128GB Max)
Network	RS485	Yes
	Alarm	1Ch Input, 1Ch Output
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
Others	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
	Ethernet	100Mbps
Others	PoE	Yes
	Power Supply	DC12V/~600mA / PoE/~8.5W
	Work Environment	-30 C ~50 C, 10%~90% Humidity

